




Outdoor Loose Tube Armoured Fiber Cables

96 Core SingleMode LooseTube Outdoor Armoured Cable

Overview



Forteq 96 Core Singlemode Glass Yarn Outdoor Loose Tube, G.657A1 PE, Armoured, Yellow,
PN: OFA096PESM-N

Forteq 96 Core Singlemode Glass Yarn Outdoor Loose Tube, G.657A1 LSZH, Armoured, Yellow,
PN: OFA096LSSM-N

Fiber Parameters

No.	Items		Unit	Specification
				G.657A1
1	Mode Field Diameter	1310nm	μm	9.0±0.4
		1550nm	μm	10.1±0.5
2	Cladding Diameter		μm	124.8±0.7
3	Cladding Non-Circularity		%	≤0.7
4	Core-Cladding Concentricity Error		μm	≤0.5
5	Coating Diameter		μm	245±5
6	Coating Non-Circularity		%	≤6.0
7	Cladding-Coating Concentricity Error		μm	≤12.0
8	Cable Cutoff Wavelength		nm	$\lambda_{cc} \leq 1260$
9	Attenuation(max.)	1310nm	dB/km	≤0.4
		1550nm	dB/km	≤0.3
10	Macro-Bending Loss	1turn×10mm radius @1550nm	dB	≤0.75
		1turn×10mm radius @1625nm	dB	≤1.5



Outdoor Loose Tube Armoured Fiber Cables

96 Core SingleMode LooseTube Outdoor Armoured Cable

Cable Parameters

Items		Specifications
Fiber Count		96
Coloured Coating Fiber	Dimension	250μm±15μm
	Colour	Blue, Orange, Green, Brown, Grey, White, Red, Black, Yellow, Purple, Pink, Aqua
Loose Tube	Dimension	2.0mm±0.05mm
	Material	PBT
	Colour	Blue, Orange, Green, Brown, Grey, White, Red, Black
Central Strength Member	Dimension	3.2mm
	Material	1.5mm Steel Wire + PE
Outer Jacket	Dimension	12.5mm±0.3mm
	Material	PE / LSZH
	Colour	Black

Mechanical and Environmental Characteristics

Items	Unit	Specifications
Tension (Long Term)	N	600
Tension (Short Term)	N	1500
Crush (Long Term)	N/10cn	300
Crush (Short Term)	N/10cn	1000
Min. Bend Radius (Dynamic)	mm	20D
Min. Bend Radius (Static)	mm	10D
Installation Temperature	°C	-20 ~ ± 60
Operating Temperature	°C	-40 ~ ± 70
Storage Temperature	°C	-40 ~ ± 70